



Darba spiediens  
10 bar  
Vides temperatūra  
Max. +90 °C  
Vielas temperatūra  
max. +90 °C  
Materiāls  
Brass with a bare metal surface

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītne 1    | Vītne 2    | L1<br>mm | L2<br>mm | L3<br>mm | SW    |
|----------------|------------|------------|----------|----------|----------|-------|
| K- 07 35 11 26 | M 14 x 1.5 | M 14 x 1.5 | 23.0     | 9.0      | 9.0      | 17 mm |
| K- 07 35 11 27 | M 16 x 1.5 | M 16 x 1.5 | 23.0     | 9.0      | 9.0      | 19 mm |
| K- 07 35 11 28 | M 24 x 1.5 | M 24 x 1.5 | 40.0     | 16.0     | 16.0     | 27 mm |
| K- 07 40 00 04 | M 5        | M 5        | 13.0     | 5.0      | 5.0      | 7 mm  |
| K- 07 40 00 05 | M 5        | G 1/8      | 17.0     | 5.0      | 7.0      | 14 mm |
| K- 07 40 00 06 | M 5        | G 1/4      | 21.0     | 7.0      | 9.0      | 17 mm |
| K- 07 40 00 01 | G 1/8      | G 1/8      | 21.0     | 8.0      | 8.0      | 14 mm |
| K- 07 40 00 02 | G 1/8      | G 1/4      | 22.0     | 9.0      | 8.0      | 17 mm |
| K- 07 40 00 03 | G 1/8      | G 3/8      | 25.0     | 9.0      | 11.0     | 19 mm |
| K- 07 40 00 07 | G 1/4      | G 1/4      | 23.0     | 9.0      | 9.0      | 17 mm |
| K- 07 40 00 31 | G 1/4 ccw  | G 1/4 ccw  | 25.0     | 10.0     | 10.0     | 17 mm |
| K- 07 40 00 08 | G 1/4      | G 3/8      | 24.0     | 9.0      | 10.0     | 19 mm |
| K- 07 40 00 09 | G 1/4      | G 1/2      | 29.0     | 11.0     | 12.0     | 24 mm |
| K- 07 40 00 10 | G 3/8      | G 3/8      | 25.0     | 10.0     | 10.0     | 19 mm |
| K- 07 40 00 32 | G 3/8 ccw  | G 3/8 ccw  | 37.0     | 13.5     | 13.5     | 19 mm |
| K- 07 40 00 11 | G 3/8      | G 1/2      | 27.0     | 10.0     | 12.0     | 24 mm |
| K- 07 40 00 12 | G 3/8      | G 3/4      | 36.0     | 12.0     | 16.0     | 32 mm |
| K- 07 40 00 13 | G 1/2      | G 1/2      | 29.0     | 12.0     | 12.0     | 24 mm |
| K- 07 40 00 14 | G 1/2      | G 3/4      | 33.0     | 12.0     | 12.0     | 32 mm |
| K- 07 40 00 15 | G 1/2      | G 1        | 40.0     | 16.0     | 16.0     | 36 mm |
| K- 07 40 00 16 | G 3/4      | G 3/4      | 33.0     | 12.0     | 12.0     | 32 mm |
| K- 07 40 00 17 | G 3/4      | G 1        | 40.0     | 16.0     | 16.0     | 36 mm |
| K- 07 40 00 18 | G 1        | G 1        | 42.5     | 17.0     | 17.0     | 36 mm |
| K- 07 40 00 19 | G 1        | G 1 1/4    | 32.0     | 14.0     | 12.0     | 42 mm |
| K- 07 40 00 20 | G 1        | G 1 1/2    | 39.0     | 14.5     | 14.5     | 50 mm |
| K- 07 40 44 36 | G 1        | G 2        | 42.0     | 18.0     | 15.0     | 60 mm |
| K- 07 40 00 21 | G 1 1/4    | G 1 1/4    | 39.0     | 16.0     | 16.0     | 42 mm |
| K- 07 40 00 22 | G 1 1/4    | G 1 1/2    | 40.5     | 15.0     | 18.0     | 50 mm |
| K- 07 40 44 37 | G 1 1/4    | G 2        | 43.0     | 29.5     | 29.5     | 60 mm |
| K- 07 40 00 23 | G 1 1/2    | G 1 1/2    | 50.0     | 20.0     | 20.0     | 50 mm |
| K- 07 40 00 24 | G 1 1/2    | G 2        | 43.0     | 17.0     | 17.0     | 62 mm |
| K- 07 40 00 25 | G 2        | G 2        | 50.0     | 20.0     | 20.0     | 62 mm |
| K- 07 40 44 38 | G 2        | G 2 1/2    | 54.0     | 24.0     | 19.0     | 77 mm |
| K- 07 40 44 39 | G 2        | G 3        | 50.0     | 20.0     | 20.0     | 89 mm |
| K- 07 40 44 40 | G 2 1/2    | G 2 1/2    | 59.0     | 24.0     | 24.0     | 77 mm |
| K- 07 40 44 41 | G 2 1/2    | G 3        | 52.5     | 20.0     | 22.5     | 89 mm |
| K- 07 40 44 42 | G 3        | G 3        | 60.0     | 24.5     | 24.5     | 89 mm |