



Darba spiediens
10 bar
Vides temperatūra
Max. +90 °C
Vielas temperatūra
max. +90 °C
Materiāls
Brass with a bare metal surface

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne 1	Vītne 2	L1 mm	L2 mm	L3 mm	SW
K- 07 35 11 26	M 14 x 1.5	M 14 x 1.5	23.0	9.0	9.0	17 mm
K- 07 35 11 27	M 16 x 1.5	M 16 x 1.5	23.0	9.0	9.0	19 mm
K- 07 35 11 28	M 24 x 1.5	M 24 x 1.5	40.0	16.0	16.0	27 mm
K- 07 40 00 04	M 5	M 5	13.0	5.0	5.0	7 mm
K- 07 40 00 05	M 5	G 1/8	17.0	5.0	7.0	14 mm
K- 07 40 00 06	M 5	G 1/4	21.0	7.0	9.0	17 mm
K- 07 40 00 01	G 1/8	G 1/8	21.0	8.0	8.0	14 mm
K- 07 40 00 02	G 1/8	G 1/4	22.0	9.0	8.0	17 mm
K- 07 40 00 03	G 1/8	G 3/8	25.0	9.0	11.0	19 mm
K- 07 40 00 07	G 1/4	G 1/4	23.0	9.0	9.0	17 mm
K- 07 40 00 31	G 1/4 ccw	G 1/4 ccw	25.0	10.0	10.0	17 mm
K- 07 40 00 08	G 1/4	G 3/8	24.0	9.0	10.0	19 mm
K- 07 40 00 09	G 1/4	G 1/2	29.0	11.0	12.0	24 mm
K- 07 40 00 10	G 3/8	G 3/8	25.0	10.0	10.0	19 mm
K- 07 40 00 32	G 3/8 ccw	G 3/8 ccw	37.0	13.5	13.5	19 mm
K- 07 40 00 11	G 3/8	G 1/2	27.0	10.0	12.0	24 mm
K- 07 40 00 12	G 3/8	G 3/4	36.0	12.0	16.0	32 mm
K- 07 40 00 13	G 1/2	G 1/2	29.0	12.0	12.0	24 mm
K- 07 40 00 14	G 1/2	G 3/4	33.0	12.0	12.0	32 mm
K- 07 40 00 15	G 1/2	G 1	40.0	16.0	16.0	36 mm
K- 07 40 00 16	G 3/4	G 3/4	33.0	12.0	12.0	32 mm
K- 07 40 00 17	G 3/4	G 1	40.0	16.0	16.0	36 mm
K- 07 40 00 18	G 1	G 1	42.5	17.0	17.0	36 mm
K- 07 40 00 19	G 1	G 1 1/4	32.0	14.0	12.0	42 mm
K- 07 40 00 20	G 1	G 1 1/2	39.0	14.5	14.5	50 mm
K- 07 40 44 36	G 1	G 2	42.0	18.0	15.0	60 mm
K- 07 40 00 21	G 1 1/4	G 1 1/4	39.0	16.0	16.0	42 mm
K- 07 40 00 22	G 1 1/4	G 1 1/2	40.5	15.0	18.0	50 mm
K- 07 40 44 37	G 1 1/4	G 2	43.0	29.5	29.5	60 mm
K- 07 40 00 23	G 1 1/2	G 1 1/2	50.0	20.0	20.0	50 mm
K- 07 40 00 24	G 1 1/2	G 2	43.0	17.0	17.0	62 mm
K- 07 40 00 25	G 2	G 2	50.0	20.0	20.0	62 mm
K- 07 40 44 38	G 2	G 2 1/2	54.0	24.0	19.0	77 mm
K- 07 40 44 39	G 2	G 3	50.0	20.0	20.0	89 mm
K- 07 40 44 40	G 2 1/2	G 2 1/2	59.0	24.0	24.0	77 mm
K- 07 40 44 41	G 2 1/2	G 3	52.5	20.0	22.5	89 mm
K- 07 40 44 42	G 3	G 3	60.0	24.5	24.5	89 mm