



Darba spiediens
10 bar
Vides temperatūra
Max. +90 °C
Vielas temperatūra
max. +90 °C

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | SW |
|----------------|------------|----------|-------|
| K- 07 40 34 45 | G 1/8 | 3.5 | 15 mm |
| K- 07 40 34 46 | G 1/4 | 3.5 | 17 mm |
| K- 07 40 34 47 | G 3/8 | 4.5 | 19 mm |
| K- 07 40 34 48 | G 1/2 | 5.0 | 24 mm |
| K- 07 40 34 49 | G 3/4 | 5.0 | 32 mm |
| K- 07 40 34 50 | G 1 | 6.0 | 41 mm |
| K- 07 40 44 33 | G 1 1/4 | 8.5 | 50 mm |
| K- 07 40 44 34 | G 1 1/2 | 8.5 | 60 mm |
| K- 07 40 44 35 | G 2 | 11.0 | 70 mm |
| K- 07 40 34 51 | M 10 x 1 | 4.0 | 14 mm |
| K- 07 40 34 52 | M 12 x 1 | 5.0 | 17 mm |
| K- 07 40 34 54 | M 14 x 1 | 4.0 | 19 mm |
| K- 07 40 34 55 | M 16 x 1 | 5.0 | 22 mm |
| K- 07 40 34 56 | M 20 x 1.5 | 4.5 | 27 mm |
| K- 07 40 34 57 | M 22 x 1 | 4.5 | 27 mm |
| K- 07 40 34 58 | M 28 x 1,5 | 6.0 | 36 mm |