



Darba spiediens  
10 bar  
Vides temperatūra  
Max. +90 °C  
Vielas temperatūra  
max. +90 °C  
Materiāls  
Brass with a bare metal surface

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	SW	uzmavuzgrieznim	šlūtenei
K- 07 40 13 84	M 5	15.5	5.0	7 mm	LW 4 mm	LW 4 mm
K- 07 40 13 86	G 1/8	41.5	9.0	14 mm	LW 6 mm	LW 6 mm
K- 07 40 49 70	G 1/8	36.0	7.0	14 mm	LW 8 mm	LW 8 mm
K- 07 40 49 16	G 1/4	39.0	9.0	17 mm	LW 8 mm	LW 8 mm
K- 07 40 49 20	G 1/4	39.0	9.0	17 mm	LW 10 mm	LW 10 mm
K- 07 40 13 72	G 3/8	48.5	10.0	19 mm	LW 4 mm	LW 4 mm
K- 07 40 13 73	G 3/8	48.5	10.0	19 mm	LW 6 mm	LW 6 mm
K- 07 40 49 26	G 3/8	39.0	9.0	19 mm	LW 8 mm	LW 8 mm
K- 07 40 14 02	G 3/8 left	48.5	10.0	19 mm	LW 6 mm	LW 6 mm
K- 07 40 49 29	G 3/8	39.0	9.0	19 mm	LW 10 mm	LW 10 mm
K- 07 40 14 03	G 3/8 left	48.5	10.0	19 mm	LW 9 mm	LW 9 mm
K- 07 40 49 36	G 1/2	42.0	11.0	24 mm	LW 8 mm	LW 8 mm
K- 07 40 49 39	G 1/2	42.0	11.0	24 mm	LW 10 mm	LW 10 mm
K- 07 40 49 54	G 3/4	54.0	12.0	32 mm	LW 25 mm	LW 25 mm
K- 07 40 49 56	G 1	55.0	13.0	38 mm	LW 19 mm	LW 19 mm
K- 07 40 13 83	G 1	57.0	12.0	38 mm	LW 32 mm	LW 32 mm
K- 07 40 49 61	G 1 1/4	61.0	14.0	50 mm	LW 32 mm	LW 32 mm
K- 07 40 49 62	G 1 1/4	68.5	15.0	42 mm	LW 38 mm	LW 38 mm
K- 07 40 49 63	G 1 1/2	67.0	15.0	55 mm	LW 32 mm	LW 32 mm
K- 07 40 49 64	G 1 1/2	71.0	15.0	55 mm	LW 38 mm	LW 38 mm
K- 07 40 49 65	G 1 1/2	71.0	15.0	55 mm	LW 50 mm	LW 50 mm
K- 07 40 49 66	G 2	88.0	20.0	70 mm	LW 50 mm	LW 50 mm