


K-RD NIPPEL KURZ 1

Reducing nipples, short type



Darba spiediens
10 bar
Vides temperatūra
Max. +90 °C
Vielas temperatūra
max. +90 °C
Materiāls
Brass with a bare metal surface

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Iekšējā vītne	Ārējā vītne	L1 mm	L2 mm	SW
K- 07 35 11 21	M 10 x 1	M 14 x 1.5	11.0	7.0	17 mm
K- 07 35 11 22	M 16 x 1.5	M 24 x 1.5	24.0	16.0	27 mm
K- 07 40 00 48	M 5	G 1/8	11.0	7.0	14 mm
K- 07 40 00 49	M 5	G 1/4	14.0	10.0	17 mm
K- 07 40 00 50	G 1/8	G 1/4	13.0	8.0	17 mm
K- 07 40 00 53	G 1/8	G 3/8	13.0	9.5	19 mm
K- 07 40 40 83	G 1/4	G 3/8	13.0	9.5	19 mm
K- 07 40 00 55	G 1/8	G 1/2	18.0	12.0	24 mm
K- 07 40 00 54	G 1/4	G 1/2	15.5	11.5	22 mm
K- 07 40 00 51	G 3/8	G 1/2	15.5	11.5	22 mm
K- 07 40 44 30	G 1/4	G 3/4	18.0	12.0	27 mm
K- 07 40 00 56	G 3/8	G 3/4	18.0	12.0	32 mm
K- 07 40 00 52	G 1/2	G 3/4	21.0	14.0	32 mm
K- 07 40 00 57	G 1/2	G 1	24.0	16.0	36 mm
K- 07 40 40 84	G 3/4	G 1	18.0	12.0	36 mm
K- 07 40 44 31	G 3/4	G 1 1/4	23.0	16.0	42 mm
K- 07 40 00 58	G 1	G 1 1/4	24.0	16.0	42 mm
K- 07 40 44 32	G 3/4	G 1 1/2	24.0	16.0	50 mm
K- 07 40 00 59	G 1	G 1 1/2	24.0	16.0	48 mm
K- 07 40 00 60	G 1 1/4	G 1 1/2	21.0	15.0	50 mm
K- 07 40 00 61	G 1	G 2	28.0	18.0	62 mm
K- 07 40 00 62	G 1 1/4	G 2	26.5	18.0	62 mm
K- 07 40 00 63	G 1 1/2	G 2	30.0	20.0	65 mm