

K-VTST 3 AB MS

Distributor pieces, brass, with 3 outlets



Ekspluatācijas spiediens
maks. 10 bar
Savienojums
G 3/4 and G 1 incl. PTFE-sealing at outer thread, G 1 1/4 without sealing

Apraksts

For assembling compressed air taps. End fittings with 1 x male and 1 x female thread, outlets optionally with male or female thread.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Ieejas pieslēgums | Izejas pieslēgums | C mm | L mm |
|----------------|-------------------|-------------------|---------|---------|
| K- 07 40 40 55 | 2 x 3/4 | 3 x 1/2 male | 50.0 | 160.0 |
| K- 07 40 40 56 | 2 x 3/4 | 3 x 1/2 female | 50.0 | 160.0 |
| K- 07 40 40 57 | 2 x 1 | 3 x 1/2 male | 50.0 | 163.0 |
| K- 07 40 40 58 | 2 x 1 | 3 x 1/2 female | 50.0 | 163.0 |
| K- 07 40 40 59 | 2 x 1 1/4 | 3 x 1/2 male | 60.0 | 197.0 |
| K- 07 40 40 60 | 2 x 1 1/4 | 3 x 1/2 female | 60.0 | 197.0 |