

# K-W135 STECK VB 20-63 INFI

135°-elbow push-in connector Ø 20 mm – Ø 63 mm



Darba vides  
Compressed air, vacuum, inert gases  
Eksploatācijas spiediens  
-0,99 bar - 15 bar  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvgredzens  
NBR  
Blīvējums  
NBR  
Drošības gredzens  
Technopolymer  
Korpuss  
Nickel-plated brass  
Spīlgredzens  
Stainless steel 1.4301  
Uzgrieznis  
Nickel-plated brass

## Produkts

Apzīmējums	Caurules ārējais Ø	B mm	C mm	E mm	L mm	SW1 mm	SW2 mm
K- 07 40 53 62	20 mm	31.5	12.5	34.5	44.0	21	30
K- 07 40 53 63	25 mm	38.5	13.5	42.5	52.0	26	35
K- 07 40 53 64	32 mm	46.0	15.0	52.0	61.0	34	45
K- 07 40 53 65	40 mm	52.0	18.0	63.0	70.0	41	55
K- 07 40 53 66	50 mm	63.5	20.0	73.0	83.5	50	65
K- 07 40 54 99	63 mm	57.5	24.0	94.0	82.0	73	75