

# K-W90 STECK VB 20-63 INFI

90°-elbow push-in connector Ø 20 mm – Ø 63 mm



Darba vides  
Compressed air, vacuum, inert gases  
Eksploatācijas spiediens  
-0,99 bar - 15 bar  
Temperatūras diapazons  
-20 °C to +80 °C  
Blīvgredzens  
NBR  
Blīvējums  
NBR  
Drošības gredzens  
Technopolymer  
Korpuss  
Nickel-plated brass  
Spīlgredzens  
Stainless steel 1.4301  
Uzgrieznis  
Nickel-plated brass

## Produkts

Apzīmējums	Caurules ārējais Ø	B mm	C mm	E mm	L mm	SW1 mm	SW2 mm
K- 07 40 53 56	20 mm	31.5	19.0	34.5	51.0	21	30
K- 07 40 53 57	25 mm	38.5	23.0	42.5	61.5	26	35
K- 07 40 53 58	32 mm	46.0	28.0	52.0	74.5	34	45
K- 07 40 53 59	40 mm	52.0	34.0	63.0	86.5	41	55
K- 07 40 53 60	50 mm	63.5	40.5	73.0	104.0	50	65
K- 07 40 54 98	63 mm	57.5	55.5	94.0	113.0	73	75