



Ekspluatācijas spiediens
Max. 16 bar (at +20 °C)
Ekspluatācijas temperatūra
-20 °C to +70 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR, siliconefree
Piespiedējgredzens
Hostaform (black nickel-plated for Ø 10, 12)
Spīļžoklis
Stainless steel AISI 316

Apraksts

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | Šļūtenes ārējam Ø | SW |
|----------------|--------|----------|-------------------|--------|
| K- 07 40 29 22 | M 5 | 20.5 | 4 mm | - |
| K- 07 40 29 23 | M 5 | 22.5 | 6 mm | - |
| K- 07 40 29 30 | G 1/8 | 20.0 | 4 mm | 9.0 mm |
| K- 07 40 29 31 | G 1/8 | 24.0 | 6 mm | 11 mm |
| K- 07 40 29 32 | G 1/8 | 26.5 | 8 mm | 13 mm |
| K- 07 40 29 27 | G 1/4 | 21.0 | 4 mm | 9.0 mm |
| K- 07 40 29 28 | G 1/4 | 24.0 | 6 mm | 11 mm |
| K- 07 40 29 29 | G 1/4 | 25.0 | 8 mm | 13 mm |
| K- 07 40 29 26 | G 1/4 | 29.5 | 10 mm | 16 mm |
| K- 07 40 29 35 | G 3/8 | 25.0 | 8 mm | 13 mm |
| K- 07 40 29 33 | G 3/8 | 29.5 | 10 mm | 16 mm |
| K- 07 40 29 34 | G 3/8 | 31.0 | 12 mm | 18 mm |
| K- 07 40 29 24 | G 1/2 | 30.0 | 10 mm | 16 mm |
| K- 07 40 29 25 | G 1/2 | 31.0 | 12 mm | 18 mm |