


K-SCHOTT-STECKVERB 4

Female bulkhead connectors

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējam Ø	SW
K- 07 40 47 16	M 8 x 0.75	18.4	3 mm	10 mm
K- 07 40 25 50	M 11 x 1	30.6	4 mm	13 mm
K- 07 40 25 52	M 14 x 1	33.5	5 mm	17 mm
K- 07 40 25 53	M 13 x 1	33.0	6 mm	16 mm
K- 07 40 25 56	M 15 x 1	35.7	8 mm	17 mm
K- 07 40 25 59	M 17 x 1	39.2	10 mm	20 mm
K- 07 40 25 60	M 20 x 1	40.7	12 mm	24 mm
K- 07 40 25 61	M 24 x 1	45.9	14 mm	27 mm