


Female bulkhead connectors, unequal



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 25 51	M 13 x 1	32.7	4 mm / 6 mm	16 mm
K- 07 40 25 54	M 15 x 1	34.4	4 mm / 8 mm	17 mm
K- 07 40 25 55	M 15 x 1	35.0	6 mm / 8 mm	17 mm
K- 07 40 25 57	M 17 x 1	37.5	6 mm / 10 mm	20 mm
K- 07 40 25 58	M 17 x 1	37.8	8 mm / 10 mm	20 mm
K- 07 40 47 17	M 20 x 1	40.8	10 mm / 12 mm	24 mm
K- 07 40 47 18	M 20 x 1	39.0	6 mm / 12 mm	24 mm
K- 07 40 47 19	M 20 x 1	40.1	8 mm / 12 mm	24 mm