


K-STECKVERSCHR AGR-K SK

Male connectors, conical male thread with outer hex



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vitnes	L1 mm	Sešstūra iedobe mm	Šļūtenes ārējam Ø	SW
K- 07 40 24 76	R 1/8	18.5	3.0	4 mm	10 mm
K- 07 40 24 77	R 1/8	22.5	4.0	6 mm	12 mm
K- 07 40 24 78	R 1/8	26.0	5.0	8 mm	13 mm
K- 07 40 24 74	R 1/4	22.3	4.0	6 mm	12 mm
K- 07 40 24 75	R 1/4	25.5	6.0	8 mm	14 mm
K- 07 40 24 73	R 1/4	28.9	7.0	10 mm	16 mm
K- 07 40 24 81	R 3/8	24.9	6.0	8 mm	14 mm
K- 07 40 24 79	R 3/8	28.9	7.0	10 mm	16 mm
K- 07 40 24 80	R 3/8	27.0	10.0	12 mm	19 mm
K- 07 40 24 72	R 1/2	26.6	10.0	12 mm	19 mm