


# K-STECKVERSCHR AGR-K SK BESCH

Male connectors, conical male thread, coated with outer hex



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 26	R 1/8	22.5	4 mm	10 mm
K- 07 40 27 27	R 1/8	24.5	6 mm	11 mm
K- 07 40 27 28	R 1/8	27.5	8 mm	13 mm
K- 07 40 47 62	R 1/4	22.5	4 mm	14 mm
K- 07 40 27 24	R 1/4	24.5	6 mm	14 mm
K- 07 40 27 25	R 1/4	27.5	8 mm	13 mm
K- 07 40 27 23	R 1/4	32.5	10 mm	16 mm
K- 07 40 47 61	R 1/4	32.5	12 mm	17 mm
K- 07 40 27 30	R 3/8	28.0	8 mm	17 mm
K- 07 40 27 29	R 3/8	32.5	10 mm	17 mm
K- 07 40 47 63	R 3/8	30.5	12 mm	17 mm
K- 07 40 47 60	R 1/2	33.0	12 mm	22 mm