



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | Šļūtenes ārējais Ø | SW    |
|----------------|--------|----------|--------------------|-------|
| K- 07 40 25 06 | M 5    | 15.7     | 3 mm               | 7 mm  |
| K- 07 40 25 12 | G 1/8  | 26.2     | 4 mm               | 10 mm |
| K- 07 40 25 13 | G 1/8  | 27.5     | 5 mm               | 12 mm |
| K- 07 40 25 14 | G 1/8  | 27.1     | 6 mm               | 12 mm |
| K- 07 40 25 15 | G 1/8  | 28.1     | 8 mm               | 13 mm |
| K- 07 40 25 09 | G 1/4  | 28.6     | 4 mm               | 10 mm |
| K- 07 40 47 15 | G 1/4  | 29.5     | 5 mm               | 12 mm |
| K- 07 40 25 10 | G 1/4  | 29.3     | 6 mm               | 12 mm |
| K- 07 40 25 11 | G 1/4  | 30.0     | 8 mm               | 14 mm |
| K- 07 40 25 08 | G 1/4  | 31.8     | 10 mm              | 16 mm |
| K- 07 40 25 16 | G 3/8  | 36.8     | 10 mm              | 16 mm |
| K- 07 40 25 17 | G 3/8  | 37.0     | 12 mm              | 19 mm |
| K- 07 40 25 07 | G 1/2  | 40.5     | 12 mm              | 19 mm |