



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | Šļūtenes ārējam Ø | SW |
|----------------|--------|----------|-------------------|-------|
| K- 07 40 25 06 | M 5 | 15.7 | 3 mm | 7 mm |
| K- 07 40 25 12 | G 1/8 | 26.2 | 4 mm | 10 mm |
| K- 07 40 25 13 | G 1/8 | 27.5 | 5 mm | 12 mm |
| K- 07 40 25 14 | G 1/8 | 27.1 | 6 mm | 12 mm |
| K- 07 40 25 15 | G 1/8 | 28.1 | 8 mm | 13 mm |
| K- 07 40 25 09 | G 1/4 | 28.6 | 4 mm | 10 mm |
| K- 07 40 47 15 | G 1/4 | 29.5 | 5 mm | 12 mm |
| K- 07 40 25 10 | G 1/4 | 29.3 | 6 mm | 12 mm |
| K- 07 40 25 11 | G 1/4 | 30.0 | 8 mm | 14 mm |
| K- 07 40 25 08 | G 1/4 | 31.8 | 10 mm | 16 mm |
| K- 07 40 25 16 | G 3/8 | 36.8 | 10 mm | 16 mm |
| K- 07 40 25 17 | G 3/8 | 37.0 | 12 mm | 19 mm |
| K- 07 40 25 07 | G 1/2 | 40.5 | 12 mm | 19 mm |