


K-STECKVERSCHR IG SK MINI

Male connectors, female thread with outer hex, mini



Darba spiediens
Max. 10 bar, vacuum
Darba vides
Saspiests gaiss
ieteicamās šļūtenes
PU or PA (nylon)
Pieteikums platība
Air, vacuum
Standarts
M thread acc. to DIN 13-1, with O-Ring
G thread acc. to DIN EN ISO 228-1, with O-Ring
R thread acc. to ISO 7-1, thread coating
Temperatūras diapazons
0 °C to +60 °C
Blīvēšanas virsma
O-ring (NBR)
Materiāls
Plastic, Nickel plated brass
Piespiedējgredzens
Plastic

Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | šļūtenes ārējam Ø | SW |
|----------------|--------|----------|-------------------|------|
| K- 07 40 49 99 | M 3 | 16.7 | 3 mm | 8 mm |
| K- 07 40 50 00 | M 3 | 18.0 | 4 mm | 8 mm |
| K- 07 40 50 01 | M 5 | 16.2 | 3 mm | 8 mm |
| K- 07 40 50 02 | M 5 | 18.0 | 4 mm | 8 mm |