


# K-STECKVERSCHR IG SK MINI

Male connectors, female thread with outer hex, mini



Darba spiediens  
Max. 10 bar, vacuum  
Darba vides  
Saspiests gaiss  
ieteicamās šļūtenes  
PU or PA (nylon)  
Pieteikums platība  
Air, vacuum  
Standarts  
M thread acc. to DIN 13-1, with O-Ring  
G thread acc. to DIN EN ISO 228-1, with O-Ring  
R thread acc. to ISO 7-1, thread coating  
Temperatūras diapazons  
0 °C to +60 °C  
Blīvēšanas virsma  
O-ring (NBR)  
Materiāls  
Plastic, Nickel plated brass  
Piespiedējgredzens  
Plastic

## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	šļūtenes ārējam Ø	SW
K- 07 40 49 99	M 3	16.7	3 mm	8 mm
K- 07 40 50 00	M 3	18.0	4 mm	8 mm
K- 07 40 50 01	M 5	16.2	3 mm	8 mm
K- 07 40 50 02	M 5	18.0	4 mm	8 mm