



Ekspluatācijas temperatūra  
Max. 150 °C  
Spiediens  
Max. 60 bar  
Materiāls  
Niķelēts misiņš

## Apraksts

Suitable for air, water, oil, steam, etc.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 49 72	G 1/8	36.0	7.0	14 mm	LW 6 mm
K- 07 40 49 73	G 1/8	36.0	7.0	14 mm	LW 8 mm
K- 07 40 49 74	G 1/8	36.0	7.0	14 mm	LW 9 mm
K- 07 40 49 15	G 1/4	36.0	9.0	17 mm	LW 4 mm
K- 07 40 49 18	G 1/4	39.0	9.0	17 mm	LW 6 mm
K- 07 40 49 19	G 1/4	39.0	9.0	17 mm	LW 8 mm
K- 07 40 49 23	G 1/4	39.0	9.0	17 mm	LW 9 mm
K- 07 40 49 24	G 1/4	39.0	9.0	17 mm	LW 10 mm
K- 07 40 49 25	G 1/4	42.0	9.0	17 mm	LW 13 mm
K- 07 40 49 28	G 3/8	39.0	9.0	19 mm	LW 8 mm
K- 07 40 49 32	G 3/8	39.0	9.0	19 mm	LW 9 mm
K- 07 40 49 33	G 3/8	39.0	9.0	19 mm	LW 10 mm
K- 07 40 49 35	G 3/8	42.0	9.0	19 mm	LW 13 mm
K- 07 40 49 38	G 1/2	42.0	11.0	24 mm	LW 8 mm
K- 07 40 49 41	G 1/2	42.0	11.0	24 mm	LW 9 mm
K- 07 40 49 42	G 1/2	42.0	11.0	24 mm	LW 10 mm
K- 07 40 49 47	G 1/2	45.0	11.0	24 mm	LW 13 mm
K- 07 40 49 48	G 1/2	53.0	11.0	24 mm	LW 16 mm
K- 07 40 49 49	G 1/2	53.0	11.0	24 mm	LW 19 mm
K- 07 40 49 50	G 3/4	51.0	12.0	32 mm	LW 13 mm
K- 07 40 49 51	G 3/4	51.0	12.0	32 mm	LW 16 mm
K- 07 40 49 53	G 3/4	54.0	12.0	32 mm	LW 19 mm
K- 07 40 49 55	G 3/4	54.0	12.0	32 mm	LW 25 mm
K- 07 40 49 60	G 1	49.0	15.0	34 mm	LW 25 mm
K- 07 40 49 68	G 1	55.0	13.0	38 mm	LW 32 mm