



Ekspluatācijas temperatūra  
Max. 150 °C  
Spiediens  
Max. 60 bar  
Materiāls  
Niķelēts misiņš

## Apraksts

Suitable for air, water, oil, steam, etc.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 13 44	R 1/8	31.5	8.0	12 mm	LW 6 mm
K- 07 40 13 45	R 1/8	31.5	8.0	12 mm	LW 8 mm
K- 07 40 13 46	R 1/8	31.5	8.0	12 mm	LW 9 mm
K- 07 40 13 47	R 1/8	32.5	8.0	12 mm	LW 10 mm
K- 07 40 13 48	R 1/4	35.0	11.0	14 mm	LW 6 mm
K- 07 40 13 49	R 1/4	35.0	11.0	14 mm	LW 8 mm
K- 07 40 13 50	R 1/4	35.0	11.0	14 mm	LW 9 mm
K- 07 40 13 51	R 1/4	36.0	11.0	14 mm	LW 10 mm
K- 07 40 13 52	R 1/4	36.0	11.0	14 mm	LW 12 mm
K- 07 40 49 75	R 1/4	39.5	11.5	14 mm	LW 13 mm
K- 07 40 13 53	R 3/8	35.5	11.5	17 mm	LW 9 mm
K- 07 40 13 54	R 3/8	36.5	11.5	17 mm	LW 10 mm
K- 07 40 13 55	R 3/8	36.5	11.5	17 mm	LW 12 mm
K- 07 40 49 77	R 3/8	41.0	13.0	17 mm	LW 13 mm
K- 07 40 13 56	R 1/2	38.5	14.0	22 mm	LW 9 mm
K- 07 40 13 57	R 1/2	39.5	14.0	22 mm	LW 10 mm
K- 07 40 13 58	R 1/2	39.5	14.0	22 mm	LW 12 mm
K- 07 40 49 78	R 1/2	44.5	15.5	22 mm	LW 13 mm
K- 07 40 49 79	R 1/2	44.5	15.5	22 mm	LW 16 mm
K- 07 40 49 80	R 1/2	44.5	15.5	22 mm	LW 19 mm