



Ekspluatācijas temperatūra  
Max. 150 °C  
Spiediens  
Max. 60 bar  
Materiāls  
Niķelēts misiņš

## Apraksts

Suitable for air, water, oil, steam, etc.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 11 76	G 1/8	28.0	8.5	12 mm	LW 6 mm
K- 07 40 11 77	G 1/8	28.0	8.5	12 mm	LW 8 mm
K- 07 40 11 78	G 1/8	28.0	8.5	12 mm	LW 9 mm
K- 07 40 11 79	G 1/8	28.0	8.5	12 mm	LW 10 mm
K- 07 40 11 80	G 1/4	33.0	10.0	15 mm	LW 6 mm
K- 07 40 11 81	G 1/4	33.0	10.0	15 mm	LW 8 mm
K- 07 40 11 82	G 1/4	33.0	10.0	15 mm	LW 9 mm
K- 07 40 11 83	G 1/4	33.0	10.0	15 mm	LW 10 mm
K- 07 40 11 84	G 1/4	33.0	10.0	15 mm	LW 12 mm
K- 07 40 11 85	G 3/8	35.0	12.0	19 mm	LW 8 mm
K- 07 40 11 86	G 3/8	35.0	12.0	19 mm	LW 10 mm
K- 07 40 11 87	G 3/8	35.0	12.0	19 mm	LW 12 mm
K- 07 40 11 88	G 3/8	35.0	12.0	19 mm	LW 14 mm
K- 07 40 11 89	G 1/2	38.0	14.0	25 mm	LW 10 mm
K- 07 40 11 90	G 1/2	41.0	14.0	25 mm	LW 12 mm
K- 07 40 11 91	G 1/2	41.0	14.0	25 mm	LW 14 mm