

K-L-MEHRFACHVERT 2 DR AGR OR CLICK

Multiple union elbows with inner hex, 2 outlets, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
NBR
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | Šļūtenes ārējais Ø | SW |
|----------------|--------|----------|----------|--------------------|------|
| K- 07 40 26 50 | M 5 | 30.3 | 20.2 | 4 mm | 2 mm |
| K- 07 40 26 51 | M 5 | 30.3 | 23.5 | 6 mm | 2 mm |
| K- 07 40 26 55 | G 1/8 | 40.9 | 20.2 | 4 mm | 3 mm |
| K- 07 40 47 28 | G 1/8 | 42.0 | 25.0 | 5 mm | 5 mm |
| K- 07 40 26 56 | G 1/8 | 40.9 | 23.5 | 6 mm | 3 mm |
| K- 07 40 26 57 | G 1/8 | 40.9 | 24.8 | 8 mm | 3 mm |
| K- 07 40 26 53 | G 1/4 | 47.0 | 23.0 | 6 mm | 4 mm |
| K- 07 40 26 54 | G 1/4 | 47.0 | 26.5 | 8 mm | 4 mm |
| K- 07 40 26 52 | G 1/4 | 47.0 | 31.4 | 10 mm | 4 mm |