

# K-L-STECKVER AG-K

Male elbows, conical male thread

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 25 65	R 1/8	18.6	16.0	4 mm	10 mm
K- 07 40 25 66	R 1/8	21.9	16.0	6 mm	10 mm
K- 07 40 25 67	R 1/8	25.4	16.0	8 mm	10 mm
K- 07 40 25 63	R 1/4	21.9	18.5	6 mm	10 mm
K- 07 40 25 64	R 1/4	25.4	18.5	8 mm	10 mm
K- 07 40 25 62	R 1/4	27.2	22.0	10 mm	14 mm