

# K-L-STECKVER DREH AG-K

Male elbows, swivel type, conical male thread



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 27 08	R 1/8	18.6	19.8	4 mm	12 mm
K- 07 40 27 09	R 1/8	21.9	19.8	6 mm	12 mm
K- 07 40 27 10	R 1/8	25.4	19.8	8 mm	12 mm
K- 07 40 27 05	R 1/4	18.6	22.6	4 mm	14 mm
K- 07 40 27 06	R 1/4	21.9	22.6	6 mm	14 mm
K- 07 40 27 07	R 1/4	25.4	23.6	8 mm	14 mm
K- 07 40 27 04	R 1/4	27.2	26.3	10 mm	14 mm
K- 07 40 27 13	R 3/8	23.6	27.1	8 mm	17 mm
K- 07 40 27 11	R 3/8	27.2	27.1	10 mm	17 mm
K- 07 40 27 12	R 3/8	30.0	27.1	12 mm	17 mm
K- 07 40 27 03	R 1/2	30.0	31.9	12 mm	22 mm