

# K-L-STECKVER DREH AG-K BESCH 1

Male elbows, swivel type, conical male thread, coated



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Iespilēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.&lt;br&gt;All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	šļūtenes ārējam Ø	SW
K- 07 40 28 10	R 1/8	20.0	20.0	4 mm	13 mm
K- 07 40 28 11	R 1/8	21.0	20.0	6 mm	13 mm
K- 07 40 28 12	R 1/8	24.0	20.0	8 mm	13 mm
K- 07 40 28 07	R 1/4	20.0	25.0	4 mm	14 mm
K- 07 40 28 08	R 1/4	21.0	25.0	6 mm	14 mm
K- 07 40 28 09	R 1/4	24.0	25.0	8 mm	14 mm
K- 07 40 28 06	R 1/4	27.0	26.0	10 mm	16 mm
K- 07 40 28 14	R 3/8	24.0	28.0	8 mm	18 mm
K- 07 40 28 13	R 3/8	27.0	30.0	10 mm	18 mm
K- 07 40 48 00	R 3/8	29.0	32.5	12 mm	20 mm
K- 07 40 47 99	R 1/2	29.0	35.5	12 mm	22 mm