

K-L-STECKVER DREH AG-K BESCH 1

Male elbows, swivel type, conical male thread, coated



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +150 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Nickel-plated brass

Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.
All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | šļūtenes ārējam Ø | SW |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 28 10 | R 1/8 | 20.0 | 20.0 | 4 mm | 13 mm |
| K- 07 40 28 11 | R 1/8 | 21.0 | 20.0 | 6 mm | 13 mm |
| K- 07 40 28 12 | R 1/8 | 24.0 | 20.0 | 8 mm | 13 mm |
| K- 07 40 28 07 | R 1/4 | 20.0 | 25.0 | 4 mm | 14 mm |
| K- 07 40 28 08 | R 1/4 | 21.0 | 25.0 | 6 mm | 14 mm |
| K- 07 40 28 09 | R 1/4 | 24.0 | 25.0 | 8 mm | 14 mm |
| K- 07 40 28 06 | R 1/4 | 27.0 | 26.0 | 10 mm | 16 mm |
| K- 07 40 28 14 | R 3/8 | 24.0 | 28.0 | 8 mm | 18 mm |
| K- 07 40 28 13 | R 3/8 | 27.0 | 30.0 | 10 mm | 18 mm |
| K- 07 40 48 00 | R 3/8 | 29.0 | 32.5 | 12 mm | 20 mm |
| K- 07 40 47 99 | R 1/2 | 29.0 | 35.5 | 12 mm | 22 mm |