

K-L-STECKVER SK AGR OR

Banjo elbows with outer hex, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +150 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
FKM (FPM)
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Nickel-plated brass

Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.
All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 92	M 5	18.0	17.5	4 mm	8 mm
K- 07 40 27 93	M 5	19.0	17.5	5 mm	8 mm
K- 07 40 27 94	M 5	19.5	19.5	6 mm	8 mm
K- 07 40 27 98	G 1/8	20.5	28.0	4 mm	14 mm
K- 07 40 27 99	G 1/8	23.0	28.0	6 mm	14 mm
K- 07 40 28 00	G 1/8	24.5	28.0	8 mm	14 mm
K- 07 40 27 96	G 1/4	24.0	33.0	6 mm	17 mm
K- 07 40 27 97	G 1/4	26.0	33.0	8 mm	17 mm
K- 07 40 27 95	G 1/4	27.0	33.0	10 mm	17 mm
K- 07 40 28 02	G 3/8	27.0	36.0	8 mm	19 mm
K- 07 40 47 94	G 3/8	28.0	36.0	10 mm	19 mm
K- 07 40 28 01	G 3/8	29.0	36.0	12 mm	19 mm
K- 07 40 47 93	G 1/2	34.5	42.0	12 mm	24 mm