

# K-L-STECK VERS DER AG OR

Male branch tees, angled plug connections, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 24 67	G 1/8	18.6	37.7	4 mm	12 mm
K- 07 40 24 68	G 1/8	21.9	41.0	6 mm	12 mm
K- 07 40 24 69	G 1/8	25.4	44.5	8 mm	12 mm
K- 07 40 24 65	G 1/4	21.9	43.0	6 mm	14 mm
K- 07 40 24 66	G 1/4	25.4	47.5	8 mm	14 mm
K- 07 40 24 64	G 1/4	27.2	49.0	10 mm	14 mm
K- 07 40 24 70	G 3/8	27.2	54.3	10 mm	17 mm
K- 07 40 24 71	G 3/8	30.0	57.1	12 mm	17 mm
K- 07 40 24 63	G 1/2	30.0	60.7	12 mm	22 mm