

# K-L-STECK VERS DER AG OR

Male branch tees, angled plug connections, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +80 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
NBR  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Hostaform

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | L1<br>mm | L2<br>mm | Šļūtenes ārējam Ø | SW    |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 24 67 | G 1/8  | 18.6     | 37.7     | 4 mm              | 12 mm |
| K- 07 40 24 68 | G 1/8  | 21.9     | 41.0     | 6 mm              | 12 mm |
| K- 07 40 24 69 | G 1/8  | 25.4     | 44.5     | 8 mm              | 12 mm |
| K- 07 40 24 65 | G 1/4  | 21.9     | 43.0     | 6 mm              | 14 mm |
| K- 07 40 24 66 | G 1/4  | 25.4     | 47.5     | 8 mm              | 14 mm |
| K- 07 40 24 64 | G 1/4  | 27.2     | 49.0     | 10 mm             | 14 mm |
| K- 07 40 24 70 | G 3/8  | 27.2     | 54.3     | 10 mm             | 17 mm |
| K- 07 40 24 71 | G 3/8  | 30.0     | 57.1     | 12 mm             | 17 mm |
| K- 07 40 24 63 | G 1/2  | 30.0     | 60.7     | 12 mm             | 22 mm |