

K-L-STECK VERS DER AG OR 2

Male branch tees, angled plug connections, swivel type, parallel male thread with O-ring



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +150 °C
Materiāls
Niķelēts misiņš
Blīvgredzens
FKM (FPM)
Iespīlēšanas gredzens
Stainless steel
Piespiedējgredzens
Nickel-plated brass

Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.
All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | Šļūtenes ārējam Ø | SW |
|----------------|--------|----------|----------|-------------------|-------|
| K- 07 40 27 88 | G 1/8 | 17.5 | 35.5 | 4 mm | 13 mm |
| K- 07 40 27 89 | G 1/8 | 21.0 | 41.5 | 6 mm | 13 mm |
| K- 07 40 27 90 | G 1/8 | 23.0 | 43.0 | 8 mm | 13 mm |
| K- 07 40 27 86 | G 1/4 | 21.0 | 45.5 | 6 mm | 13 mm |
| K- 07 40 27 87 | G 1/4 | 23.0 | 47.5 | 8 mm | 13 mm |
| K- 07 40 27 85 | G 1/4 | 27.0 | 50.5 | 10 mm | 16 mm |
| K- 07 40 47 92 | G 3/8 | 23.0 | 48.5 | 8 mm | 13 mm |
| K- 07 40 27 91 | G 3/8 | 27.0 | 54.0 | 10 mm | 16 mm |
| K- 07 40 47 91 | G 3/8 | 31.0 | 57.5 | 12 mm | 18 mm |
| K- 07 40 47 90 | G 1/2 | 32.0 | 65.5 | 12 mm | 20 mm |