

# K-L-STECK VERS DER AG OR 2

Male branch tees, angled plug connections, swivel type, parallel male thread with O-ring



Darba spiediens  
Max. 16 bar  
Eksploatācijas temperatūra  
-20 °C to +150 °C  
Materiāls  
Niķelēts misiņš  
Blīvgredzens  
FKM (FPM)  
Iespīlēšanas gredzens  
Stainless steel  
Piespiedējgredzens  
Nickel-plated brass

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.<br>All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējam Ø	SW
K- 07 40 27 88	G 1/8	17.5	35.5	4 mm	13 mm
K- 07 40 27 89	G 1/8	21.0	41.5	6 mm	13 mm
K- 07 40 27 90	G 1/8	23.0	43.0	8 mm	13 mm
K- 07 40 27 86	G 1/4	21.0	45.5	6 mm	13 mm
K- 07 40 27 87	G 1/4	23.0	47.5	8 mm	13 mm
K- 07 40 27 85	G 1/4	27.0	50.5	10 mm	16 mm
K- 07 40 47 92	G 3/8	23.0	48.5	8 mm	13 mm
K- 07 40 27 91	G 3/8	27.0	54.0	10 mm	16 mm
K- 07 40 47 91	G 3/8	31.0	57.5	12 mm	18 mm
K- 07 40 47 90	G 1/2	32.0	65.5	12 mm	20 mm