



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | L1 mm | L2 mm | šļūtenes ārējam Ø |
|----------------|----------|----------|-------------------|
| K- 07 40 25 42 | 21.2 | 10.4 | 3 mm |
| K- 07 40 25 43 | 33.4 | 16.7 | 4 mm |
| K- 07 40 25 44 | 38.4 | 19.2 | 5 mm |
| K- 07 40 25 45 | 38.0 | 19.0 | 6 mm |
| K- 07 40 25 46 | 42.6 | 21.3 | 8 mm |
| K- 07 40 25 47 | 46.6 | 23.3 | 10 mm |
| K- 07 40 25 48 | 52.0 | 26.0 | 12 mm |
| K- 07 40 25 49 | 58.6 | 29.3 | 14 mm |