

K-T-STECK VERS DRE AG-K

Male branch tees, swivel type, parallel male thread



Darba spiediens
Max. 16 bar
Eksploatācijas temperatūra
-20 °C to +80 °C
Materiāls
Niķelēts misiņš
Iespilēšanas gredzens
Stainless steel
Piespiedējgredzens
Hostaform

Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	Šļūtenes ārējais Ø	SW
K- 07 40 27 18	R 1/8	37.2	19.8	4 mm	12 mm
K- 07 40 27 19	R 1/8	43.8	19.8	6 mm	12 mm
K- 07 40 27 20	R 1/8	50.8	19.8	8 mm	12 mm
K- 07 40 27 15	R 1/4	37.2	22.6	4 mm	14 mm
K- 07 40 27 16	R 1/4	43.8	22.6	6 mm	14 mm
K- 07 40 27 17	R 1/4	50.8	23.6	8 mm	14 mm
K- 07 40 27 14	R 1/4	54.4	26.3	10 mm	14 mm
K- 07 40 27 22	R 3/8	47.2	27.1	8 mm	17 mm
K- 07 40 27 21	R 3/8	54.4	27.1	10 mm	17 mm