


K-XVMK 4

Male connectors, conical male thread acc. to ISO 7-1



Darba spiediens
Max. 18 bar
Blīvējums
Buna-N
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	SW	šļūtenei
K- 07 40 31 14	R 1/8	41.0	10 mm	4 mm / 2 mm
K- 07 40 31 15	R 1/8	25.0	12 mm	5 mm / 3 mm
K- 07 40 31 16	R 1/8	26.5	12 mm	6 mm / 4 mm
K- 07 40 31 17	R 1/8	26.5	12 mm	8 mm / 6 mm
K- 07 40 31 13	R 1/8	29.5	14 mm	10 mm / 8 mm
K- 07 40 31 11	R 1/4	30.0	14 mm	6 mm / 4 mm
K- 07 40 31 12	R 1/4	30.0	14 mm	8 mm / 6 mm
K- 07 40 31 10	R 1/4	32.0	14 mm	10 mm / 8 mm
K- 07 40 31 20	R 3/8	31.5	17 mm	6 mm / 4 mm
K- 07 40 31 21	R 3/8	31.0	17 mm	8 mm / 6 mm
K- 07 40 31 18	R 3/8	33.0	17 mm	10 mm / 8 mm
K- 07 40 31 19	R 3/8	35.0	17 mm	12 mm / 10 mm
K- 07 40 31 09	R 1/2	34.5	22 mm	8 mm / 6 mm
K- 07 40 31 07	R 1/2	36.0	22 mm	10 mm / 8 mm
K- 07 40 31 08	R 1/2	38.0	22 mm	12 mm / 10 mm