



Darba spiediens
Max. 18 bar
Blīvējums
Buna-N
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | L1 mm | L2 mm | Sešstūris | SW | Šļūtenei |
|----------------|--------|----------|----------|-----------|-------|---------------|
| K- 07 40 31 52 | M 5 | 16.0 | 17.5 | Male | 8 mm | 5 mm / 3 mm |
| K- 07 40 31 53 | M 5 | 16.0 | 17.5 | Male | 8 mm | 6 mm / 4 mm |
| K- 07 40 31 61 | G 1/8 | 24.0 | 28.0 | Male | 14 mm | 5 mm / 3 mm |
| K- 07 40 31 62 | G 1/8 | 24.0 | 28.0 | Male | 14 mm | 6 mm / 4 mm |
| K- 07 40 31 63 | G 1/8 | 24.0 | 28.0 | Male | 14 mm | 8 mm / 6 mm |
| K- 07 40 31 60 | G 1/8 | 24.0 | 28.0 | Male | 14 mm | 10 mm / 8 mm |
| K- 07 40 31 58 | G 1/4 | 26.0 | 33.0 | Male | 17 mm | 6 mm / 4 mm |
| K- 07 40 31 59 | G 1/4 | 26.0 | 33.0 | Male | 17 mm | 8 mm / 6 mm |
| K- 07 40 31 57 | G 1/4 | 27.5 | 33.0 | Male | 17 mm | 10 mm / 8 mm |
| K- 07 40 31 66 | G 3/8 | 26.0 | 36.0 | Male | 19 mm | 6 mm / 4 mm |
| K- 07 40 31 67 | G 3/8 | 28.5 | 37.0 | Male | 20 mm | 8 mm / 6 mm |
| K- 07 40 31 64 | G 3/8 | 29.0 | 37.0 | Male | 20 mm | 10 mm / 8 mm |
| K- 07 40 31 65 | G 3/8 | 31.5 | 36.0 | Female | 5 mm | 12 mm / 10 mm |
| K- 07 40 31 56 | G 1/2 | 29.0 | 42.0 | Male | 24 mm | 8 mm / 6 mm |
| K- 07 40 31 54 | G 1/2 | 30.5 | 42.0 | Male | 27 mm | 10 mm / 8 mm |
| K- 07 40 31 55 | G 1/2 | 33.0 | 42.0 | Female | 8 mm | 12 mm / 10 mm |