

# K-STM-R

Banjo tees, parallel male thread with O-ring



Darba spiediens  
Max. 18 bar  
Blīvējums  
Buna-N  
Materiāls  
Niķelēts misiņš

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	SW	Šļūtenei
K- 07 40 31 94	M 5	33.0	17.5	8 mm	5 mm / 3 mm
K- 07 40 31 95	M 5	33.0	17.5	8 mm	6 mm / 4 mm
K- 07 40 32 02	G 1/8	46.0	28.0	14 mm	5 mm / 3 mm
K- 07 40 32 03	G 1/8	49.0	28.0	14 mm	6 mm / 4 mm
K- 07 40 32 04	G 1/8	50.0	28.0	14 mm	8 mm / 6 mm
K- 07 40 32 01	G 1/8	53.0	28.0	14 mm	10 mm / 8 mm
K- 07 40 31 99	G 1/4	53.0	33.0	17 mm	6 mm / 4 mm
K- 07 40 32 00	G 1/4	52.0	33.0	17 mm	8 mm / 6 mm
K- 07 40 31 98	G 1/4	55.0	33.0	17 mm	10 mm / 8 mm
K- 07 40 32 07	G 3/8	53.0	36.0	19 mm	6 mm / 4 mm
K- 07 40 32 08	G 3/8	57.0	37.0	20 mm	8 mm / 6 mm
K- 07 40 32 05	G 3/8	58.0	37.0	20 mm	10 mm / 8 mm
K- 07 40 32 06	G 3/8	64.0	37.0	20 mm	12 mm / 10 mm
K- 07 40 31 96	G 1/2	61.0	42.0	27 mm	10 mm / 8 mm
K- 07 40 31 97	G 1/2	64.0	42.0	27 mm	12 mm / 10 mm