


# K-T AG-K ISO 7-1 2 SCH

Male branch tees, conical male thread acc. to ISO 7-1



Darba spiediens  
Max. 18 bar  
Blīvējums  
Buna-N  
Materiāls  
Niķelēts misiņš

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 31 87	R 1/8	49.0	16.0	9 mm	4 mm / 2 mm
K- 07 40 31 88	R 1/8	43.0	17.0	8 mm	5 mm / 3 mm
K- 07 40 31 89	R 1/8	44.0	17.0	9 mm	6 mm / 4 mm
K- 07 40 31 90	R 1/8	44.0	17.0	10 mm	8 mm / 6 mm
K- 07 40 31 86	R 1/8	51.0	18.5	11 mm	10 mm / 8 mm
K- 07 40 31 84	R 1/4	44.0	20.0	9 mm	6 mm / 4 mm
K- 07 40 31 85	R 1/4	44.0	20.0	12 mm	8 mm / 6 mm
K- 07 40 31 83	R 1/4	50.0	21.0	12 mm	10 mm / 8 mm
K- 07 40 31 93	R 3/8	46.0	22.0	12 mm	8 mm / 6 mm
K- 07 40 31 91	R 3/8	50.0	22.0	12 mm	10 mm / 8 mm
K- 07 40 31 92	R 3/8	62.0	24.0	17 mm	12 mm / 10 mm
K- 07 40 31 81	R 1/2	57.0	28.0	17 mm	10 mm / 8 mm
K- 07 40 31 82	R 1/2	62.0	26.0	17 mm	12 mm / 10 mm