


K-XVM ZYL 2

Male connectors, parallel male thread



izmantojamās šļūtenes
PA, PE, PU
maks. ekspluatācijas spiediens
18 bar
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	SW	šļūtenei
K- 07 40 33 54	M 5	21.0	8 mm	5 mm / 3 mm
K- 07 40 33 55	M 5	21.0	8 mm	6 mm / 4 mm
K- 07 40 33 60	G 1/8	23.0	14 mm	5 mm / 3 mm
K- 07 40 33 61	G 1/8	25.5	13 mm	6 mm / 4 mm
K- 07 40 33 62	G 1/8	25.5	14 mm	8 mm / 6 mm
K- 07 40 33 59	G 1/8	27.5	14 mm	10 mm / 8 mm
K- 07 40 33 57	G 1/4	28.0	16 mm	6 mm / 4 mm
K- 07 40 33 58	G 1/4	28.0	16 mm	8 mm / 6 mm
K- 07 40 33 56	G 1/4	29.5	16 mm	10 mm / 8 mm
K- 07 40 33 65	G 3/8	29.0	19 mm	6 mm / 4 mm
K- 07 40 33 66	G 3/8	29.0	19 mm	8 mm / 6 mm
K- 07 40 33 63	G 3/8	30.5	19 mm	10 mm / 8 mm
K- 07 40 33 64	G 3/8	32.0	19 mm	12 mm / 10 mm