

K-W90 AG-K 0 OR

Male elbows, conical male thread (without O-ring)



izmantojamās šļūtenes
PA, PE, PU
maks. ekspluatācijas spiediens
18 bar
Materiāls
Niķelēts misiņš

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	L1 mm	L2 mm	SW	šļūtenei
K- 07 40 33 88	R 1/8	22.5	17.0	8 mm	6 mm / 4 mm
K- 07 40 33 89	R 1/8	22.5	17.0	10 mm	8 mm / 6 mm
K- 07 40 33 87	R 1/8	25.5	18.5	11 mm	10 mm / 8 mm
K- 07 40 33 85	R 1/4	22.5	20.0	10 mm	6 mm / 4 mm
K- 07 40 33 86	R 1/4	22.5	20.0	10 mm	8 mm / 6 mm
K- 07 40 33 84	R 1/4	25.5	21.5	11 mm	10 mm / 8 mm
K- 07 40 33 92	R 3/8	23.5	22.5	11 mm	6 mm / 4 mm
K- 07 40 33 93	R 3/8	24.0	22.5	11 mm	8 mm / 6 mm
K- 07 40 33 90	R 3/8	25.5	22.5	11 mm	10 mm / 8 mm
K- 07 40 33 91	R 3/8	30.0	24.5	14 mm	12 mm / 10 mm