

# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling



Izmantošana  
Air, gases, oils, greases, fuels, organic and inorganic substances  
Eksploatācijas temperatūra  
-40 °C to +100 °C  
Pieslēguma veids  
connection nipples and coupling NW 7,2

## Apraksts

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ø šļūtenei iekšpusē mm	Ø šļūtenei ārpusē mm	Tinumi	Ø spirālei ārpusē mm	Max. working pressure resistance at 23°C bar	maks. darba ga m
K- 07 10 12 95	6.3	7.9	15	75	13	2.5
K- 07 10 12 96	6.3	7.9	30	75	13	5.0
K- 07 10 12 97	6.3	7.9	45	75	13	7.5
K- 07 10 12 65	7.9	9.5	10	115	12	2.5
K- 07 10 12 66	7.9	9.5	20	115	12	5.0
K- 07 10 12 67	7.9	9.5	30	115	12	7.5
K- 07 10 12 68	9.5	11.8	8	140	11	2.5
K- 07 10 12 69	9.5	11.8	15	140	11	5.0
K- 07 10 12 70	9.5	11.8	23	140	11	7.5