

K-SPIR SCHL DREH VERSCHRAU

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Spiral hose, with swivel adapter and kink protector



Ekspluatācijas temperatūra
-40 °C to +74 °C

Apraksts

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Ø šļūtenei iekšpusē mm | Ø šļūtenei ārpusē mm | Ø ārējam tinumam mm | Max. working pressure resistance at 23°C bar | maks. darba garums m |
|----------------|--------|---------------------------|-------------------------|------------------------|---|-------------------------|
| K- 07 10 07 19 | G 1/4 | 5.0 | 8.0 | 40 | 10 | 3.0 |
| K- 07 10 07 20 | G 1/4 | 5.0 | 8.0 | 40 | 10 | 6.0 |
| K- 07 10 07 21 | G 1/4 | 5.0 | 8.0 | 40 | 10 | 7.5 |
| K- 07 10 07 22 | G 1/4 | 6.3 | 9.5 | 60 | 10 | 3.0 |
| K- 07 10 07 23 | G 1/4 | 6.3 | 9.5 | 60 | 10 | 6.0 |
| K- 07 10 07 24 | G 1/4 | 6.3 | 9.5 | 60 | 10 | 7.5 |
| K- 07 10 12 77 | G 1/4 | 6.3 | 9.5 | 60 | 10 | 10.0 |
| K- 07 10 07 25 | G 3/8 | 8.0 | 12.0 | 80 | 9 | 3.0 |
| K- 07 10 07 26 | G 3/8 | 8.0 | 12.0 | 80 | 9 | 6.0 |
| K- 07 10 07 27 | G 3/8 | 8.0 | 12.0 | 80 | 9 | 7.5 |
| K- 07 10 12 86 | G 3/8 | 8.0 | 12.0 | 80 | 9 | 10.0 |