



Iekšējā kārtā  
Soft-PVC, black  
Ieliktnis  
poliestera appinums  
Ārskats  
Soft-PVC, blue  
Temperatūra  
-20 °C to +60 °C  
Ru\_\_a garums  
50 m

## Apraksts

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ø šļūtenei iekšpusē mm	Ø šļūtenei ārpusē mm	Max. working pressure resistance at 23°C bar	Min. liekuma rādiuss mm
K- 07 10 10 33	6.3	11.0	15	23
K- 07 10 10 34	8.0	13.0	15	28
K- 07 10 10 35	9.0	14.5	15	32
K- 07 10 10 36	10.0	15.5	15	35
K- 07 10 10 37	12.7	19.0	15	45
K- 07 10 10 38	16.0	23.0	15	56
K- 07 10 10 39	19.0	26.5	15	67
K- 07 10 10 40	25.0	33.5	15	88