

K-W90 DRV AS-FS

Speed controllers, 90°, connection plug, with built-in indicator

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



maks. ekspluatācijas spiediens
 1 MPa
 min. ekspluatācijas spiediens
 0.10 MPa
 Vides temperatūra
 -5 °C bis +60 °C (no freezing)
 Vielas temperatūra
 -5 °C to +60 °C (ohne Gefrieren)
 Griežamās pogas krāsa
 Blue
 Indikatora loga novietojums
 0°
 Izejas
 1
 Izmēģinājuma spiediens
 1.50 MPa
 Pievadu skaits
 1
 Regulēšana
 Flow governing
 Darba vides
 Saspiests gaiss
 Šļūtenes materiāls
 polyamid, soft polyamid, polyurethane, FEP, PFA
 Sērija
 AS-FS

Produkts

Apzīmējums	Izmēģinājuma spiediens MPa	Pievadu skaits	Tipizmērs	Izejas pieslēgums	Pievada pieslēgums	Adatas apgriezieni	Modelis	Vienība
K- 07 30 30 54	1.50	1	1	for hose outer-Ø2 mm	outer thread M 5 8		with sealing ring	0.007
K- 07 30 30 57	1.50	1	1	for hose outer-Ø3.2 mm	outer thread M 5 8		with sealing ring	0.007
K- 07 30 30 55	1.50	1	1	for hose outer-Ø4 mm	outer thread M 5 8		with sealing ring	0.007
K- 07 30 30 56	1.50	1	1	for hose outer-Ø6 mm	outer thread M 5 8		with sealing ring	0.008
K- 07 30 30 62	1.50	1	2	for hose outer-Ø3.2 mm	outer thread R 1/8	10	Teflon coated	0.007
K- 07 30 30 67	1.50	1	2	for hose outer-Ø3.2 mm	outer thread R 1/4	10	Teflon coated	0.023
K- 07 30 30 58	1.50	1	2	for hose outer-Ø4 mm	outer thread R 1/8	10	Teflon coated	0.013
K- 07 30 30 63	1.50	1	2	for hose outer-Ø4 mm	outer thread R 1/4	10	Teflon coated	0.023
K- 07 30 30 59	1.50	1	2	for hose outer-Ø6 mm	outer thread R 1/8	10	Teflon coated	0.014
K- 07 30 30 68	1.50	1	2	for hose outer-Ø6 mm	outer thread G 1/8	10	surface with sealing ring	0.014
K- 07 30 30 64	1.50	1	2	for hose outer-Ø6 mm	outer thread R 1/4	10	Teflon coated	0.023
K- 07 30 30 69	1.50	1	2	for hose outer-Ø6 mm	outer thread G 1/4	10	surface with sealing ring	0.023
K- 07 30 30 60	1.50	1	2	for hose outer-Ø8 mm	outer thread R 1/8	10	Teflon coated	0.015
K- 07 30 30 65	1.50	1	2	for hose outer-Ø8 mm	outer thread R 1/4	10	Teflon coated	0.024
K- 07 30 30 70	1.50	1	2	for hose outer-Ø8 mm	outer thread G 1/4	10	surface with sealing ring	0.024

Apzīmējums	Izmēginājuma spiediens MPa	Pievadu skaits	Tipizmērs	Izejas pieslēgums	Pievada pieslēgums	Adatas apgriezieni	Modelis	Vienība
K- 07 30 30 61	1.50	1	2	for hose outer- Ø10 mm	outer thread R 1/8	10	Teflon coated	0.016
K- 07 30 30 66	1.50	1	2	for hose outer- Ø10 mm	outer thread R 1/4	10	Teflon coated	0.025
K- 07 30 30 71	1.50	1	2	for hose outer- Ø10 mm	outer thread G 1/4	10	surface with sealing ring	0.025
K- 07 30 30 72	1.50	1	3	for hose outer-Ø6 mm	outer thread R 3/8	10	Teflon coated	0.038
K- 07 30 30 76	1.50	1	3	for hose outer-Ø6 mm	outer thread G 3/8	10	surface with sealing ring	0.038
K- 07 30 30 73	1.50	1	3	for hose outer-Ø8 mm	outer thread R 3/8	10	Teflon coated	0.038
K- 07 30 30 77	1.50	1	3	for hose outer-Ø8 mm	outer thread G 3/8	10	surface with sealing ring	0.038
K- 07 30 30 74	1.50	1	3	for hose outer- Ø10 mm	outer thread R 3/8	10	Teflon coated	0.029
K- 07 30 30 78	1.50	1	3	for hose outer- Ø10 mm	outer thread G 3/8	10	surface with sealing ring	0.029
K- 07 30 30 75	1.50	1	3	for hose outer- Ø12 mm	outer thread R 3/8	10	Teflon coated	0.041
K- 07 30 30 79	1.50	1	4	for hose outer- Ø10 mm	outer thread R 1/2	10	Teflon coated	0.062
K- 07 30 30 82	1.50	1	4	for hose outer- Ø10 mm	outer thread G 1/2	10	surface with sealing ring	0.062
K- 07 30 30 80	1.50	1	4	for hose outer- Ø12 mm	outer thread R 1/2	10	Teflon coated	0.064
K- 07 30 30 83	1.50	1	4	for hose outer- Ø12 mm	outer thread G 1/2	10	surface with sealing ring	0.064
K- 07 30 30 81	1.50	1	4	for hose outer- Ø16 mm	outer thread R 1/2	10	Teflon coated	0.068
K- 07 30 30 84	1.50	1	4	for hose outer- Ø16 mm	outer thread G 1/2	10	surface with sealing ring	0.068