

K-WV 3/2 5/2 5/3 HAND

3/2, 5/2 and 5/3-way pilot valves



Ekspluatācijas spiediens
2.5 - 10 bar (monostable)
1.0 - 10 bar (bistable)
Max. vacuum 10 bar
Temperatūras diapazons
-10 °C to +60 °C
Caurplūde 6 bar un 5 bar
400 NL/min (G 1/8), 750 NL/min (G 3/8), 3200 NL/min (G 1/2)
Caurplūde 6 bar un 10 bar
550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)
Vārsta korpusa
Alumīnijs
Atspere
Special steel
Virzulis
Nickel-plated aluminium
Blīvējums
NBR

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	Funkcija	Slēguma shēmas numurs	Vadība
K- 07 15 00 70	G 1/8"	3/2-way	10	Monostabil
K- 07 15 00 71	G 1/8"	3/2-way	11	Bistabil
K- 07 15 00 72	G 1/4"	3/2-way	10	Monostabil
K- 07 15 00 73	G 1/4"	3/2-way	11	Bistabil
K- 07 15 00 74	G 1/2"	3/2-way	10	Monostabil
K- 07 15 00 75	G 1/2"	3/2-way	11	Bistabil
K- 07 15 02 29	G 1/8"	5/2-way	12	Monostabil
K- 07 15 02 30	G 1/8"	5/2-way	13	Bistabil
K- 07 15 02 31	G 1/4"	5/2-way	12	Monostabil
K- 07 15 02 32	G 1/4"	5/2-way	13	Bistabil
K- 07 15 02 33	G 1/2"	5/2-way	12	Monostabil
K- 07 15 02 34	G 1/2"	5/2-way	13	Bistabil
K- 07 15 03 57	G 1/8"	5/3-way	14	Monostabil
K- 07 15 03 58	G 1/8"	5/3-way	15	Bistabil
K- 07 15 03 59	G 1/8"	5/3-way	16	Monostabil
K- 07 15 03 60	G 1/8"	5/3-way	17	-
K- 07 15 03 61	G 1/8"	5/3-way	18	-
K- 07 15 03 62	G 1/8"	5/3-way	19	-
K- 07 15 03 63	G 1/4"	5/3-way	14	Monostabil
K- 07 15 03 64	G 1/4"	5/3-way	15	Bistabil
K- 07 15 03 65	G 1/4"	5/3-way	16	Monostabil
K- 07 15 03 66	G 1/4"	5/3-way	17	-
K- 07 15 03 67	G 1/4"	5/3-way	18	-
K- 07 15 03 68	G 1/4"	5/3-way	19	-
K- 07 15 03 69	G 1/2"	5/3-way	14	Monostabil
K- 07 15 03 70	G 1/2"	5/3-way	15	Bistabil
K- 07 15 03 71	G 1/2"	5/3-way	16	Monostabil
K- 07 15 03 72	G 1/2"	5/3-way	17	-
K- 07 15 03 73	G 1/2"	5/3-way	18	-
K- 07 15 03 74	G 1/2"	5/3-way	19	-