

K-WV 3/2 PNEUMATISCH

3/2-way pilot valves



Ekspluatācijas spiediens
Max. vacuum 10 bar
min. darba spiediens
2.5 bar (monostable), 1.0 bar (bistable)
Temperatūras diapazons
-10 °C to +60 °C
Caurplūde 6 bar un 5 bar
400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)
Caurplūde 6 bar un 10 bar
550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)
Regulēšanas gaisa pieslēgums
G 1/8

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	DN	Funkcija	Slēguma shēmas numurs	Vadība
K- 07 15 00 41	G 1/8"	5	3/-way NO	24	Monostabil
K- 07 15 00 42	G 1/4"	8	3/-way NO	24	Monostabil
K- 07 15 00 45	G 1/2"	15	3/-way NO	24	Monostabil
K- 07 15 25 67	G 3/8"	13	3/-way NO	24	Monostabil
K- 07 15 00 43	G 1/8"	5	3/2-way NC	25	Monostabil
K- 07 15 00 44	G 1/4"	8	3/2-way NC	25	Monostabil
K- 07 15 00 46	G 1/2"	15	3/2-way NC	25	Monostabil
K- 07 15 25 68	G 3/8"	13	3/2-way NC	25	Monostabil
K- 07 15 00 47	G 1/8"	5	3/2-way	26	Bistabil
K- 07 15 00 48	G 1/4"	8	3/2-way	26	Bistabil
K- 07 15 00 49	G 1/2"	15	3/2-way	26	Bistabil
K- 07 15 25 69	G 3/8"	13	3/2-way	26	Bistabil