



Ekspluatācijas spiediens
 2,5 - 10 bar (monostable)
 1,0 - 10 bar (bistable)
 vacuum up to 10 bar (external pilot air)
 min. darba spiediens
 2.5 bar (monostable), 1.0 bar (bistable)
 Temperatūras diapazons
 -10 °C to +60 °C
 Caurplūde 6 bar un 5 bar
 400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)
 Caurplūde 6 bar un 10 bar
 550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	Spriegums	DN	Funkcija	Slēguma shēmas numurs	Vadība
K- 07 15 01 93	G 1/8"	24 V DC	5	5/2-way	35	Monostabil
K- 07 15 01 94	G 1/4"	24 V DC	8	5/2-way	35	Monostabil
K- 07 15 25 81	G 3/8"	24 V DC	13	5/2-way	35	Monostabil
K- 07 15 01 95	G 1/2"	24 V DC	15	5/2-way	35	Monostabil
K- 07 15 01 96	G 1/8"	230 V, 50 Hz	5	5/2-way	35	Monostabil
K- 07 15 01 97	G 1/4"	230 V, 50 Hz	8	5/2-way	35	Monostabil
K- 07 15 25 82	G 3/8"	230 V, 50 Hz	13	5/2-way	35	Monostabil
K- 07 15 01 98	G 1/2"	230 V, 50 Hz	15	5/2-way	35	Monostabil
K- 07 15 01 99	G 1/8"	24 V DC	5	5/2-way	36	Bistabil
K- 07 15 02 00	G 1/4"	24 V DC	8	5/2-way	36	Bistabil
K- 07 15 25 83	G 3/8"	24 V DC	13	5/2-way	36	Bistabil
K- 07 15 02 01	G 1/2"	24 V DC	15	5/2-way	36	Bistabil
K- 07 15 02 02	G 1/8"	230 V, 50 Hz	5	5/2-way	36	Bistabil
K- 07 15 02 03	G 1/4"	230 V, 50 Hz	8	5/2-way	36	Bistabil
K- 07 15 25 84	G 3/8"	230 V, 50 Hz	13	5/2-way	36	Bistabil
K- 07 15 02 04	G 1/2"	230 V, 50 Hz	15	5/2-way	36	Bistabil