

# K-WV 5/3 ELEKTROPNEU MITTELSTELLUNG

5/3-way pilot valves (monostable)



Ekspluatācijas spiediens  
2,5 - 10 bar (monostable)  
1,0 - 10 bar (bistable)  
vacuum up to 10 bar (external pilot air)  
min. darba spiediens  
2.5 bar (monostable), 1.0 bar (bistable)  
Temperatūras diapazons  
-10 °C to +60 °C  
Caurplūde 6 bar un 5 bar  
400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)  
Caurplūde 6 bar un 10 bar  
550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Savienojums	Spriegums	DN	Funkcija	Slēguma shēmas numurs
K- 07 15 03 30	G 1/8"	24 V DC	5	5/3-way	37
K- 07 15 03 31	G 1/4"	24 V DC	8	5/3-way	37
K- 07 15 25 87	G 3/8"	24 V DC	13	5/3-way	37
K- 07 15 03 32	G 1/2"	24 V DC	15	5/3-way	37
K- 07 15 03 33	G 1/8"	230 V, 50 Hz	5	5/3-way	37
K- 07 15 03 34	G 1/4"	230 V, 50 Hz	8	5/3-way	37
K- 07 15 25 88	G 3/8"	230 V, 50 Hz	13	5/3-way	37
K- 07 15 03 35	G 1/2"	230 V, 50 Hz	15	5/3-way	37
K- 07 15 03 36	G 1/8"	24 V DC	5	5/3-way	38
K- 07 15 03 37	G 1/4"	24 V DC	8	5/3-way	38
K- 07 15 25 89	G 3/8"	24 V DC	13	5/3-way	38
K- 07 15 03 38	G 1/2"	24 V DC	15	5/3-way	38
K- 07 15 03 39	G 1/8"	230 V, 50 Hz	5	5/3-way	38
K- 07 15 03 40	G 1/4"	230 V, 50 Hz	8	5/3-way	38
K- 07 15 25 90	G 3/8"	230 V, 50 Hz	13	5/3-way	38
K- 07 15 03 41	G 1/2"	230 V, 50 Hz	15	5/3-way	38
K- 07 15 03 42	G 1/8"	24 V DC	5	5/3-way	39
K- 07 15 25 91	G 3/8"	24 V DC	13	5/3-way	39
K- 07 15 03 43	G 1/4"	24 V DC	8	5/3-way	39
K- 07 15 03 44	G 1/2"	24 V DC	15	5/3-way	39
K- 07 15 03 45	G 1/8"	230 V, 50 Hz	5	5/3-way	39
K- 07 15 03 46	G 1/4"	230 V, 50 Hz	8	5/3-way	39
K- 07 15 25 92	G 3/8"	230 V, 50 Hz	13	5/3-way	39
K- 07 15 03 47	G 1/2"	230 V, 50 Hz	15	5/3-way	39