

# K-WV 3/2 SCHL GEW

3/2-way valve, pipe (input) - thread (output)



Ekspluatācijas spiediens  
maks. 10 bar  
Caurplūde 6,3 bar, p=1 bar  
400 NL/min (Ø 6), 790 NL/min (Ø 8)  
Regulēšanas gaisa pieslēgums  
4 mm  
Temperatūras diapazons  
-20 °C to +60 °C  
Vārsta funkcija  
NC  
Korpuss  
Technopolymer  
Iekšējās daļas  
nickel-plated brass, brass, technopolymer, stainless steel  
Blīvējums  
NBR  
Montāža  
Wall mounting (housing with drilled holes)  
Bracket mounting (mounting bracket available)  
Panel mounting (with bracket or lock nut)  
Simbols  
on the housing

## Apraksts

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design. &lt;br&gt;All components can be installed In parallel, In series, In a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | Šļūtenes Ø<br>mm | A<br>mm | B<br>mm | I<br>mm |
|----------------|--------|------------------|---------|---------|---------|
| K- 07 15 25 50 | G 1/8  | 6                | 58.5    | 43.2    | 14.6    |
| K- 07 15 25 51 | G 1/8  | 8                | 66.2    | 49.7    | 18.7    |
| K- 07 15 25 48 | G 1/4  | 6                | 61.5    | 43.2    | 14.6    |
| K- 07 15 25 49 | G 1/4  | 8                | 70.6    | 49.7    | 18.7    |
| K- 07 15 25 52 | G 3/8  | 8                | 72.2    | 49.7    | 18.7    |