

# K-SNV ENTLUE V SCHA SCHL GEW

Quick-exhaust valves, with silencer, pipe (input) - thread (output)



Ekspluatācijas spiediens  
1 - 10 bar  
Caurplūde 6,3 bar  
50 NL/min (Ø 4), 270 NL/min (Ø 6), 400 NL/min (Ø 8)  
Caurplūde Atgaisošana 6,3 bar  
100 NL/min (Ø 4), 700 NL/min (Ø 6), 1000 NL/min (Ø 8)  
Temperatūras diapazons  
-20 °C to +60 °C  
Korpuss  
Technopolymer  
Iekšējās daļas  
nickel-plated brass, brass, &lt;br&gt;technopolymer, stainless steel  
Blīvējums  
NBR  
Montāža  
Wall mounting (housing with drilled holes)  
Bracket mounting (mounting bracket available)  
Panel mounting (with bracket or lock nut)  
Simbols  
on the housing

## Apraksts

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design. &lt;br&gt;All components can be installed In parallel, In series, In a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Vītnes | šļūtenes Ø<br>mm | A<br>mm | B<br>mm | I<br>mm |
|----------------|--------|------------------|---------|---------|---------|
| K- 07 15 25 31 | M 5    | 4                | 46.7    | 19.8    | 12.8    |
| K- 07 15 25 32 | G 1/8  | 4                | 50.6    | 19.8    | 12.8    |
| K- 07 15 20 41 | G 1/8  | 6                | 58.5    | 25.5    | 14.6    |
| K- 07 15 20 42 | G 1/8  | 8                | 66.2    | 31.5    | 18.7    |
| K- 07 15 20 39 | G 1/4  | 6                | 61.5    | 25.5    | 14.6    |
| K- 07 15 20 40 | G 1/4  | 8                | 70.6    | 31.5    | 18.7    |
| K- 07 15 20 43 | G 3/8  | 8                | 72.2    | 31.5    | 18.7    |