

K-DRV ABLD GEW C SCHLITZ

Unidirectional flow control valves, outgoing air restriction (»C«), screw connection



Ekspluatācijas spiediens
maks. 10 bar
Temperatūras diapazons
0 °C to +70 °C
Dobskrūve, pagriežama svira, regulēšanas skrūve
Nickel-plated brass
Iekšējās daļas
Brass with a bare metal surface
Blīvgredzena apmales blīvējums
NBR
Blīvējumi (nepazaudējami)
Polyamide (glass fibre-reinforced)

Apraksts

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	C mm	Savienojums	SW	Vītnes	B mm
K- 07 15 05 40	11.5	M 5 female	8 mm	M 5	24.5
K- 07 15 05 45	16.0	G 1/8 female	14 mm	G 1/8	32.0
K- 07 15 05 41	22.0	G 1/4 female	17 mm	G 1/4	40.0
K- 07 15 25 24	26.0	G 3/8 female	20 mm	G 3/8	50.0
K- 07 15 25 23	32.0	G 1/2 female	26 mm	G 1/2	61.0