

K-DRV GEW V SCHLITZ

Unidirectional flow control valves, incoming air restriction (»V«), screw connection



Ekspluatācijas spiediens
maks. 10 bar
Temperatūras diapazons
0 °C to +70 °C
Dobskrūve, pagriežama svira, regulēšanas skrūve
Nickel-plated brass
Iekšējās daļas
Brass with a bare metal surface
Blīvgredzena apmales blīvējums
NBR
Blīvējumi (nepazaudējami)
Polyamide (glass fibre-reinforced)

Apraksts

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	C mm	Savienojums	SW	Vītnes	B mm
K- 07 15 25 21	11.5	M 5 female	8 mm	M 5	24.5
K- 07 15 05 70	16.0	G 1/8 female	14 mm	G 1/8	32.0
K- 07 15 05 66	22.0	G 1/4 female	17 mm	G 1/4	40.0
K- 07 15 25 22	26.0	G 3/8 female	20 mm	G 3/8	50.0